NSN 5315-00-833-8325

Headless Straight Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-833-8325

First End Style: Chamfered Pinlength: Between 0.609 inches and 0.641 inches Pindiameter: Between 0.3129 inches and 0.3131 inches First End Taper Length: Between 0.016 inches and 0.047 inches Second End Relationship With First End: Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c First End Taper Angle: Between 43.0 degrees and 47.0 degrees Surface Finish: 32.0 microinches head bearing surface Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 400 Shelf Life: N/a Unit of Measure: - Demilitarization: No Fig: A212a0	
Pinlength: Between 0.609 inches and 0.641 inches Pindiameter: Between 0.3129 inches and 0.3131 inches First End Taper Length: Between 0.016 inches and 0.047 inches Second End Relationship With First End: Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c First End Taper Angle: Between 43.0 degrees and 47.0 degrees Surface Finish: 32.0 microinches head bearing surface Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 41	First End Style:
Between 0.609 inches and 0.641 inches Pindiameter: Between 0.3129 inches and 0.3131 inches First End Taper Length: Between 0.016 inches and 0.047 inches Second End Relationship With First End: Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c First End Taper Angle: Between 43.0 degrees and 47.0 degrees Surface Finish: 32.0 microinches head bearing surface Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 44 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Chamfered
Pindiameter: Between 0.3129 inches and 0.3131 inches First End Taper Length: Between 0.016 inches and 0.047 inches Second End Relationship With First End: Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c First End Taper Angle: Between 43.0 degrees and 47.0 degrees Surface Finish: 32.0 microinches head bearing surface Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 4140 Sheff Life: N/a Dint Of Measure: - No Fing:	Pinlength:
Between 0.3129 inches and 0.3131 inches First End Taper Length: Between 0.016 inches and 0.047 inches Second End Relationship With First End: Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c First End Taper Angle: Between 43.0 degrees and 47.0 degrees Surface Finish: 32.0 microinches head bearing surface Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 4140 Sheff Life: N/a Dint Of Measure: - Demilitarization: No Fig:	Between 0.609 inches and 0.641 inches
First End Taper Length: Between 0.016 inches and 0.047 inches Second End Relationship With First End: Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c First End Taper Angle: Between 43.0 degrees and 47.0 degrees Surface Finish: 32.0 microinches head bearing surface Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 413 Sheff Life: N/a Dint Of Measure: - No Fig:	Pindiameter:
Between 0.016 inches and 0.047 inches Second End Relationship With First End: Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c First End Taper Angle: Between 43.0 degrees and 47.0 degrees Surface Finish: 32.0 microinches head bearing surface Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 44 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.3129 inches and 0.3131 inches
Second End Relationship With First End: Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c First End Taper Angle: Between 43.0 degrees and 47.0 degrees Surface Finish: 32.0 microinches head bearing surface Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 40 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	First End Taper Length:
Identical Hardness Rating: 32.0 rockwell c and 38.0 rockwell c First End Taper Angle: Between 43.0 degrees and 47.0 degrees Surface Finish: 32.0 microinches head bearing surface 32.0 microinches head bearing surface Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 44 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.016 inches and 0.047 inches
Hardness Rating: 32.0 rockwell c and 38.0 rockwell c First End Taper Angle: Between 43.0 degrees and 47.0 degrees Surface Finish: 32.0 microinches head bearing surface Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 4140 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Second End Relationship With First End:
32.0 rockwell c and 38.0 rockwell c First End Taper Angle: Between 43.0 degrees and 47.0 degrees Surface Finish: 32.0 microinches head bearing surface Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 40 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Identical
First End Taper Angle: Between 43.0 degrees and 47.0 degrees Surface Finish: 32.0 microinches head bearing surface Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 440 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Hardness Rating:
Between 43.0 degrees and 47.0 degrees Surface Finish: 32.0 microinches head bearing surface Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 44 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	32.0 rockwell c and 38.0 rockwell c
Surface Finish: 32.0 microinches head bearing surface Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 400 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	First End Taper Angle:
32.0 microinches head bearing surface Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 40 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 43.0 degrees and 47.0 degrees
Material: Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 44 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Finish:
Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 440 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	32.0 microinches head bearing surface
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
N/a Unit Of Measure: Demilitarization: No Fiig:	Steel comp 4130 or steel comp 4135 or steel comp 4137 or steel comp 4140 or steel comp 4037
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A212a0	Fiig:
	A212a0