NSN 5315-00-834-3494

Headless Straight Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-834-3494

| First End Style: |
|--|
| Chamfered |
| Second End Style: |
| Chamfered |
| Pinlength: |
| Between 0.177 inches and 0.197 inches |
| Pindiameter: |
| Between 0.0634 inches and 0.0636 inches |
| First End Taper Length: |
| Between 0.008 inches and 0.016 inches |
| Second End Taper Length: |
| 0.021 inches |
| Features Provided: |
| Casehardened |
| Second End Relationship With First End: |
| Not identical |
| Hardness Rating: |
| 58.0 rockwell c and 64.0 rockwell c |
| First End Taper Angle: |
| Between 20.0 degrees and 30.0 degrees |
| Second End Taper Angle: |
| Between 4.0 degrees and 12.0 degrees |
| Special Features: |
| Small c.Amfer end may be 0.008 in. Min, 0.016 in.Max radius in lieu of chamfer |
| Material: |
| Steel |
| Material Specification: |
| 66 federal standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A212a0 |
| |
| |