

View Online at <https://aerobasegroup.com/nsn/5315-00-834-8401>

Head Diameter:

Between 0.360 inches and 0.450 inches

Shank Diameter:

Between 0.2470 inches and 0.2485 inches

Ring Handle Diameter:

Between 1.000 inches and 1.125 inches

Detent Quantity:

2

Actuation Method:

Lever

End Application:

Wsd: engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, tomcat f-14; helicopter, utility/search and recovery uh-1n; aircraft, stratolifter c-135; aircraft, t-38

Grip Length:

Between 1.200 inches and 1.220 inches

Actuation Type:

Pull and push

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

0.935 inches

Criticality Code Justification:

Feat

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

0.410 inches

Special Features:

Weapon system essential

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Specification Data:

80205-nas1354 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0