

View Online at <https://aerobasegroup.com/nsn/5315-00-834-8401>

**Head Diameter:**

Between 0.360 inches and 0.450 inches

**Shank Diameter:**

Between 0.2470 inches and 0.2485 inches

**Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

**Detent Quantity:**

2

**Actuation Method:**

Lever

**End Application:**

Wsd: engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, tomcat f-14; helicopter, utility/search and recovery uh-1n; aircraft, stratolifter c-135; aircraft, t-38

**Grip Length:**

Between 1.200 inches and 1.220 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

40.0 rockwell c spindle

**Shoulder To Head End Distance:**

0.935 inches

**Criticality Code Justification:**

Feat

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

0.410 inches

**Special Features:**

Weapon system essential

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Specification Data:**

80205-nas1354 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0