

View Online at <https://aerobasegroup.com/nsn/5315-00-835-1832>

**Head Diameter:**

Between 0.890 inches and 0.990 inches

**Handle Length:**

Between 2.150 inches and 2.250 inches

**Shank Diameter:**

Between 0.7470 inches and 0.7485 inches

**Ring Handle Diameter:**

Between 0.890 inches and 0.990 inches

**Detent Quantity:**

2

**Grip Length:**

Between 1.500 inches and 1.520 inches

**Actuation Type:**

Pull

**Features Provided:**

Drive out feature

**Hardness Rating:**

36.0 rockwell c spindle and 40.0 rockwell c spindle

**Shoulder To Head End Distance:**

Between 1.260 inches and 1.360 inches

**Pin Attachment Type:**

Hook

**Detent To Tapered End Distance:**

Between 0.740 inches and 0.840 inches

**Material:**

Steel comp 4130 spindle

**Material Specification:**

Mil-t-6736 military specification single material response shank or mil-s-6758 military specification single material response shank

**Surface Treatment:**

Cadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

**Style Designator:**

T handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.