NSN 5315-00-836-3398

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-836-3398 **Head Diameter:** 0.940 inches **Shank Diameter:** Between 0.4970 inches and 0.4995 inches **Ring Handle Diameter:** 1.370 inches **Actuation Method:** Push button **Grip Length:** Between 1.100 inches and 1.120 inches **Actuation Type:** Pull and push **Features Provided:** Drive out feature Hardness Rating: 54.0 rockwell c detent and 64.0 rockwell c detent **Shear Strength:** 32800 double pounds per square inch **Shoulder To Head End Distance:** 2.180 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** 0.590 inches **Special Features:** Steel attaching hook or ring with cadmium surface treatment specification qq-p-416, type 2, cl 3 Material: Steel spring **Material Specification:** Qq-w-470 federal specification single material response spring **Surface Treatment:** Passivate detent **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response shank **Specification Data:** 80205-nas1358 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5315-00-836-3398

Quick Release Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.