

View Online at <https://aerobasegroup.com/nsn/5315-00-838-1375>

**First End Style:**

Chamfered

**Second End Style:**

Slotted

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.370 inches

**Shank Length:**

0.590 inches

**Shoulder Diameter:**

Between 0.309 inches and 0.312 inches

**Shank Diameter:**

0.190 inches

**Overall Length:**

4.030 inches

**Internal Drive Style:**

Slot

**Second End Slot Width:**

Between 0.040 inches and 0.055 inches

**First End Taper Length:**

0.125 inches

**Second End Slot Depth:**

Between 0.050 inches and 0.055 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

34.0 rockwell c

**Thread Size:**

0.190 inches

**First End Location:**

Shank end

**First End Taper Angle:**

15.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.