NSN 5315-00-839-0812

Headless Shoulder Pin - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5315-00-839-0812



First End Style: Chamfered **Second End Style:** Radius **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.280 inches and 0.320 inches **Shank Length:** Between 0.520 inches and 0.540 inches **Shoulder Width Across Flats:** Between 0.367 inches and 0.376 inches **Shank Diameter:** 0.125 inches **Overall Length:** Between 1.600 inches and 1.645 inches **Hole Arrangement Style:** One end drilled First Hole Diameter: Between 0.065 inches and 0.072 inches Distance From Centerline Of Hole To End Of Pin: Between 0.100 inches and 0.130 inches **Second End Corner Radius:** Between 0.005 inches and 0.015 inches First End Taper Length: Between 0.020 inches and 0.050 inches Second End Relationship With First End: Not identical Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Thread Size:** 0.190 inches **Second Shank Diameter:** 0.188 inches **First End Location:** Threaded end First End Taper Angle: 45.0 degrees **Second Shank Length:**

Between 0.520 inches and 0.540 inches

NSN 5315-00-839-0812

Headless Shoulder Pin - Page 2 of 2



Material:
Steel comp 410
Material Specification:
Ams 5613 assn standard single material response
Style Designator:
Shoulder
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A212a0