

View Online at <https://aerobasegroup.com/nsn/5315-00-844-3662>

Overall Length:

Between 0.735 inches and 0.765 inches

Diameter:

Between 0.258 inches and 0.264 inches

Material Thickness:

0.048 inches

End Application:

W/s: aircraft, c-2a (reprocured); lvs power unit mk48 and trailer family; stream (std. Tensioned replenishment at sea method); armored security vehicle, model xm1117; shipboard material handling equipment (mhe); helicopter, carrier based asw, sh-60f; helicopter, search and rescue, hh-60h; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); helicopter, advance attack, ah-1w; helicopter, mh-53e

Hardness Rating:

46.0 rockwell c and 53.0 rockwell c

Shear Strength:

7700 double pound

Material:

Steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1086 or steel comp 1095

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty2 cl2 federal specification single treatment response

Style Designator:

Slotted

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0