

View Online at <https://aerobasegroup.com/nsn/5315-00-844-3662>

**Overall Length:**

Between 0.735 inches and 0.765 inches

**Diameter:**

Between 0.258 inches and 0.264 inches

**Material Thickness:**

0.048 inches

**End Application:**

W/s: aircraft, c-2a (reprocured); lvs power unit mk48 and trailer family; stream (std. Tensioned replenishment at sea method); armored security vehicle, model xm1117; shipboard material handling equipment (mhe); helicopter, carrier based asw, sh-60f; helicopter, search and rescue, hh-60h; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); helicopter, advance attack, ah-1w; helicopter, mh-53e

**Hardness Rating:**

46.0 rockwell c and 53.0 rockwell c

**Shear Strength:**

7700 double pound

**Material:**

Steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1086 or steel comp 1095

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, ty2 cl2 federal specification single treatment response

**Style Designator:**

Slotted

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0