

View Online at <https://aerobasegroup.com/nsn/5315-00-844-3956>

Overall Length:

Between 0.610 inches and 0.640 inches

Diameter:

Between 0.099 inches and 0.103 inches

Material Thickness:

0.022 inches

End Application:

W/s: ssbn mk-118 fire control sys; helicopter, carrier based asw, sh-60f; consolidated targets; trainer, b-1b aircraft; helicopter, mh-53e; missile, strategic air to ground (sram ii); boilers, 1200 psi; missile, advanced medium range air-to-air (amraam)/aim120a; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); helicopter, advance attack, ah-1w

Hardness Rating:

46.0 rockwell c and 53.0 rockwell c

Shear Strength:

1000 double pound

Material:

Steel comp 1070 or steel comp 1074 or steel comp 1080 or steel comp 1086 or steel comp 1095

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty2 cl2 federal specification single treatment response

Style Designator:

Slotted

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-p-10971 spec.