NSN 5315-00-844-9728

Headless Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-844-9728 First End Style: Chamfered **Overall Length:** 3.812 inches Diameter: Between 0.6239 inches and 0.6249 inches **Effective Length:** 3.062 inches **Undercut Diameter:** Between 0.593 inches and 0.599 inches **Undercut Width:** Between 0.039 inches and 0.042 inches **Second Undercut Width:** Between 0.039 inches and 0.042 inches First End Taper Length: 0.031 inches Second End Relationship With First End: Identical **Hardness Rating:** 32.0 rockwell c and 35.0 rockwell c **First End Location:** Both ends First End Taper Angle: 45.0 degrees **Surface Finish:** 63.0 microinches outside diameter Material: Steel comp 4140 or steel comp 8640 or steel comp 4140 or steel comp 8640 **Material Specification:** Astm a-331 assn standard all material responses **Surface Treatment:** Phosphate manganese or phosphate zinc **Surface Treatment Specification:** Mil-p-16232 type m class 1 military specification 1st treatment response or mil-p-16232 type z class 1 military specification 2nd treatment response **Style Designator:** Groove Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5315-00-844-9728

Headless Grooved Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-p-16232 spec.