## NSN 5315-00-849-2081

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-849-2081

First End Style: Chamfered Second End Style: Slotted Thread Class: 2a **Thread Direction: Right-hand Thread Length:** 0.281 inches Shank Length: 0.344 inches **Shoulder Width Across Flats:** Between 0.249 inches and 0.250 inches Shank Diameter: Between 0.112 inches and 0.235 inches **Overall Length:** Between 0.781 inches and 0.813 inches Second End Slot Width: 0.062 inches First End Taper Length: 0.031 inches Second End Slot Depth: 0.310 inches Second End Relationship With First End: Not identical **Thread Size:** 0.112 inches Second Shank Diameter: Between 0.112 inches and 0.235 inches **First End Location:** Threaded end First End Taper Angle: 45.0 degrees Second Shank Length: 0.391 inches Material: Steel comp 303 **Material Specification:** Qq-s-764, cond a federal specification single material response **Surface Treatment:** 

Passivate

## NSN 5315-00-849-2081

Headless Shoulder Pin - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0