# NSN 5315-00-849-6892

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-849-6892

#### Head Diameter:

Between 0.510 inches and 0.630 inches

#### Shank Diameter:

Between 0.3720 inches and 0.3735 inches

#### **Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

#### **Detent Quantity:**

2

# **Actuation Method:**

Push button

Grip Length:

Between 2.300 inches and 2.320 inches

# Actuation Type:

Pull and push

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

# Shoulder To Head End Distance:

1.000 inches

Pin Attachment Type:

Hook

Detent To Tapered End Distance:

Between 0.460 inches and 0.510 inches

#### Material:

Steel comp 4130 spindle

#### **Material Specification:**

Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

#### Surface Treatment:

Cadmium spindle and chromate spindle

## Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

#### Style Designator:

Ring handle

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A212a0

## Mil-std (military Standard):

Mil-t-6736 spec.