

View Online at <https://aerobasegroup.com/nsn/5315-00-850-4785>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.370 inches and 0.510 inches

**Shank Length:**

Between 0.460 inches and 0.540 inches

**Shoulder Width Across Flats:**

Between 0.365 inches and 0.385 inches

**Shank Diameter:**

Between 0.180 inches and 0.190 inches

**Overall Length:**

Between 1.390 inches and 1.410 inches

**First End Taper Length:**

0.125 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.190 inches

**Second Shank Diameter:**

Between 0.180 inches and 0.190 inches

**First End Location:**

Shank end

**First End Taper Angle:**

30.0 degrees

**Surface Finish:**

125.000 microinches

**Second Shank Length:**

Between 0.720 inches and 0.840 inches

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758, cond c4 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.