

View Online at <https://aerobasegroup.com/nsn/5315-00-850-4785>

First End Style:

Chamfered

Second End Style:

Chamfered

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.370 inches and 0.510 inches

Shank Length:

Between 0.460 inches and 0.540 inches

Shoulder Width Across Flats:

Between 0.365 inches and 0.385 inches

Shank Diameter:

Between 0.180 inches and 0.190 inches

Overall Length:

Between 1.390 inches and 1.410 inches

First End Taper Length:

0.125 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.190 inches

Second Shank Diameter:

Between 0.180 inches and 0.190 inches

First End Location:

Shank end

First End Taper Angle:

30.0 degrees

Surface Finish:

125.000 microinches

Second Shank Length:

Between 0.720 inches and 0.840 inches

Material:

Steel comp 4130

Material Specification:

Mil-s-6758, cond c4 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.