NSN 5315-00-855-9066

Headed Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-855-9066

First End Style: Chamfered Head Style: Knurled no. 1 Diameter: Between 0.490 inches and 0.494 inches Effective Length: Between 1.190 inches and 1.210 inches Undercut Diameter: Between 0.365 inches and 0.385 inches Under Head Length: Between 1.460 inches and 1.580 inches Undercut Radius: Between 0.010 inches and 0.030 inches
Head Style:Knurled no. 1Diameter:Between 0.490 inches and 0.494 inchesEffective Length:Between 1.190 inches and 1.210 inchesUndercut Diameter:Between 0.365 inches and 0.385 inchesUnder Head Length:Between 1.460 inches and 1.580 inchesUndercut Radius:Between 0.010 inches and 0.030 inches
Knurled no. 1 Diameter: Between 0.490 inches and 0.494 inches Effective Length: Between 1.190 inches and 1.210 inches Undercut Diameter: Between 0.365 inches and 0.385 inches Under Head Length: Between 1.460 inches and 1.580 inches Undercut Radius: Between 0.010 inches and 0.030 inches
Diameter: Between 0.490 inches and 0.494 inches Effective Length: Between 1.190 inches and 1.210 inches Undercut Diameter: Between 0.365 inches and 0.385 inches Under Head Length: Between 1.460 inches and 1.580 inches Undercut Radius: Between 0.010 inches and 0.030 inches
Between 0.490 inches and 0.494 inches Effective Length: Between 1.190 inches and 1.210 inches Undercut Diameter: Between 0.365 inches and 0.385 inches Under Head Length: Between 1.460 inches and 1.580 inches Undercut Radius: Between 0.010 inches and 0.030 inches
Effective Length: Between 1.190 inches and 1.210 inches Undercut Diameter: Between 0.365 inches and 0.385 inches Under Head Length: Between 1.460 inches and 1.580 inches Undercut Radius: Between 0.010 inches and 0.030 inches
Between 1.190 inches and 1.210 inches Undercut Diameter: Between 0.365 inches and 0.385 inches Under Head Length: Between 1.460 inches and 1.580 inches Undercut Radius: Between 0.010 inches and 0.030 inches
Undercut Diameter: Between 0.365 inches and 0.385 inches Under Head Length: Between 1.460 inches and 1.580 inches Undercut Radius: Between 0.010 inches and 0.030 inches
Between 0.365 inches and 0.385 inches Under Head Length: Between 1.460 inches and 1.580 inches Undercut Radius: Between 0.010 inches and 0.030 inches
Under Head Length: Between 1.460 inches and 1.580 inches Undercut Radius: Between 0.010 inches and 0.030 inches
Between 1.460 inches and 1.580 inches Undercut Radius: Between 0.010 inches and 0.030 inches
Undercut Radius: Between 0.010 inches and 0.030 inches
Between 0.010 inches and 0.030 inches
Hale American sement Studes
Hole Arrangement Style:
Drilled through head
First Hole Diameter:
Between 0.124 inches and 0.129 inches
Distance From Centerline Of Hole To End Of Pin:
Between 1.650 inches and 1.770 inches
First End Taper Length:
Between 0.170 inches and 0.230 inches
Grip Length:
Between 1.240 inches and 1.280 inches
First End Taper Angle:
29.5 degrees
Pin Head Diameter:
Between 0.590 inches and 0.650 inches
Surface Finish:
125.0 microinches
Height:
Between 0.350 inches and 0.410 inches
Material:
Steel comp 431
Material Specification:
Mil-s-18732, cond ht-115 military specification single material
Style Designator:
Groove
Shelf Life:
N/a
Unit Of Measure:

response

NSN 5315-00-855-9066

Headed Grooved Pin - Page 2 of 2

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-18732 spec.

