NSN 5315-00-861-1465

Machine Key - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-861-1465

view online at https://aerobasegroup.com/hsh/ss1/ss1s-ou-ou1-1405
Counterbore Diameter:
Between 0.781 inches and 0.812 inches
Counterbore Depth:
Between 0.605 inches and 0.625 inches
Overall Length:
2.875 inches
Overall Height:
Between 1.484 inches and 1.500 inches
Overall Width:
Between 1.246 inches and 1.248 inches
First Flat Length:
Between 2.574 inches and 2.575 inches
Flat Height:
Between 0.980 inches and 1.000 inches
Mounting Hole Diameter:
Between 0.516 inches and 0.532 inches
Mounting Hole Depth:
Between 0.980 inches and 1.000 inches
Key Chamfer Length:
Between 0.150 inches and 0.180 inches
Hardness Rating:
38.0 rockwell c and 53.03 rockwell c
Criticality Code Justification:
Abmk
Distance From Mounting Hole Center To End:
Between 1.265 inches and 1.281 inches
Starting Edge Shape:
Chamfered
Key Chamfer Angle:
45.0 degrees
Mounting Hole Type And Quantity:
1 unthreaded-counterbored
Special Features:
$Mounting \ hole \ 0.516 \ in. \ Min., \ 0.532 \ in. \ Max., \ w1/0/688 \ in. \ Counterbore \ spaced \ 0.531 \ in. \ C \ to \ c \ of \ first \ mounting \ hole \ and \ centered \ 0.734 \ in. \ C \ do \ c \ of \ first \ mounting \ hole \ do \ content \ do \ c \ of \ first \ mounting \ hole \ do \ content \ do \ c \ of \ first \ mounting \ hole \ do \ content \ do \ c \ of \ first \ mounting \ hole \ do \ content \ do \ c \ of \ first \ mounting \ hole \ do \ content \ do \ c \ of \ first \ mounting \ hole \ do \ content \ do \ c \ of \ first \ mounting \ hole \ do \ c \ of \ first \ mounting \ hole \ do \ content \ do \ c \ of \ first \ mounting \ hole \ do \ content \ do \ c \ of \ first \ mounting \ hole \ do \ content \ do \ c \ of \ first \ mounting \ hole \ do \ content \ do \ c \ of \ first \ mounting \ hole \ do \ content \ do \ c \ of \ first \ mounting \ hole \ do \ content \ do \ c \ of \ first \ mounting \ hole \ do \ content \ do \ c \ of \ first \ mounting \ hole \ do \ content \ do \ c \ of \ first \ mounting \ hole \ do \ c \ of \ first \ mounting \ hole \ do \ c \ of \ first \ mounting \ hole \ do \ c \ of \ first \ mounting \ hole \ do \ c \ of \ first \ mounting \ hole \ do \ c \ of \ first \ mounting \ hole \ do \ c \ of \ first \ mounting \ hole \ do \ c \ of \ first \ mounting \ hole \ do \ d$
Min., 0.750 in. Maximum from end and corners of second flat have 0.040 in. Min., 0.050 in. Maximum radius
Material:
Steel
Style Designator:
Stepped
Shelf Life:

--

N/a

Unit Of Measure:

NSN 5315-00-861-1465

Machine Key - Page 2 of 2



Demilitarization:

No

Fiig:

A212a0