

View Online at <https://aerobasegroup.com/nsn/5315-00-871-9679>

**First End Style:**

Square

**Second End Style:**

Slotted

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.369 inches

**Shank Length:**

0.531 inches

**Shoulder Diameter:**

1.375 inches

**Shank Diameter:**

0.233 inches

**Overall Length:**

1.437 inches

**Second End Slot Width:**

0.064 inches

**Second End Slot Depth:**

0.125 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Thread Size:**

0.250 inches

**Second Shank Diameter:**

0.233 inches

**First End Location:**

Threaded end

**Second Shank Length:**

0.840 inches

**Special Features:**

0.062 in. Lg by 0.190 in. Diameter groove located 0.100 in. From shoulder on first end

**Material:**

Steel comp 4340

**Material Specification:**

Mil-s-5000 cond c military specification single material response

**Surface Treatment:**

Oxide

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5000 spec.