## NSN 5315-00-871-9679

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-871-9679 First End Style: Square **Second End Style:** Slotted **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.369 inches **Shank Length:** 0.531 inches **Shoulder Diameter:** 1.375 inches **Shank Diameter:** 0.233 inches **Overall Length:** 1.437 inches Second End Slot Width: 0.064 inches **Second End Slot Depth:** 0.125 inches Second End Relationship With First End: Not identical Hardness Rating: 39.0 rockwell c and 43.0 rockwell c **Thread Size:** 0.250 inches **Second Shank Diameter:** 0.233 inches First End Location: Threaded end **Second Shank Length:** 0.840 inches **Special Features:** 0.062 in. Lg by 0.190 in. Diameter groove located 0.100 in. From shoulder onfirst end Material: Steel comp 4340 **Material Specification:** Mil-s-5000 cond c military specification single material response

**Surface Treatment:** 

Oxide

## NSN 5315-00-871-9679

Headless Shoulder Pin - Page 2 of 2



Shoulder
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0

Mil-std (military Standard):

Mil-s-5000 spec.

Style Designator: