NSN 5315-00-881-3223

First End Style: Chamfered

Second End Style:

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-881-3223

| Pointed |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.310 inches |
| Shank Length: |
| 0.680 inches |
| Shoulder Diameter: |
| 0.500 inches |
| Shank Diameter: |
| 0.253 inches |
| Overall Length: |
| 1.620 inches |
| Hole Arrangement Style: |
| One end drilled |
| First Hole Diameter: |
| 0.250 inches |
| Distance From Centerline Of Hole To End Of Pin: |
| 0.500 inches |
| First End Taper Length: |
| 0.045 inches |
| Second End Taper Length: |
| 0.320 inches |
| Second End Relationship With First End: |
| Not identical |
| Thread Size: |
| 0.250 inches |
| First End Location: |
| Threaded end |
| First End Taper Angle: |
| 45.0 degrees |
| Second End Taper Angle: |
| 60.0 degrees |
| Special Features: |
| 0.120 in. Spherical radius on pointed end |
| Material: |
| Steel comp 4140 |

NSN 5315-00-881-3223

Headless Shoulder Pin - Page 2 of 2



| Material Specification: |
|--|
| Mil-s-5626 military specification single material response |
| Style Designator: |
| Shoulder |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A212a0

Mil-s-5626 spec.

Mil-std (military Standard):