

View Online at <https://aerobasegroup.com/nsn/5315-00-886-6164>

**Head Diameter:**

Between 0.310 inches and 0.530 inches

**Shank Diameter:**

Between 0.2470 inches and 0.2485 inches

**Ring Handle Diameter:**

1.060 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

W/s: support equipment, mx peacekeeper missile; missile, all-weather anti-ship, harpoon (agm-84); engine, aircraft, f100-pw-200 (f-16a/b/c/d)

**Grip Length:**

Between 1.400 inches and 1.420 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shoulder To Head End Distance:**

0.780 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

Between 0.260 inches and 0.290 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0