## NSN 5315-00-886-6164

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-886-6164 **Head Diameter:** Between 0.310 inches and 0.530 inches **Shank Diameter:** Between 0.2470 inches and 0.2485 inches **Ring Handle Diameter:** 1.060 inches **Detent Quantity:** 2 **Actuation Method:** Push button **End Application:** W/s: support equipment, mx peacekeeper missile; missile, all-weather anti-ship, harpoon (agm-84); engine, aircraft, f100-pw-200 (f-16a/b/c/d) **Grip Length:** Between 1.400 inches and 1.420 inches **Actuation Type:** Push **Hardness Rating:** 40.0 rockwell c spindle **Shoulder To Head End Distance:** 0.780 inches Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** Between 0.260 inches and 0.290 inches Material: Steel comp 630 spindle or steel comp 632 spindle **Material Specification:** Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle **Surface Treatment:** Passivate spindle **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spindle **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure:** 

Fiig:

No

A212a0

**Demilitarization:**