## NSN 5315-00-890-0056



Quick Release Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-00-890-0056 **Shank Diameter:** Between 0.2470 inches and 0.2495 inches **Actuation Method:** Push button **Grip Length:** Between 0.500 inches and 0.520 inches **Actuation Type:** Push **Features Provided:** Lock open feature Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Shear Strength:** 8200 double pounds per square inch **Shoulder To Head End Distance:** 1.550 inches Pin Center To Handle End Distance: 1.780 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** 0.380 inches Material: Steel comp 440c detent **Material Specification:** Qq-s-763 federal specification single material response detent **Surface Treatment:** Oxide film head or anodize head **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response shank **Style Designator:** L handle **Specification Data:** 80205-nas1334 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A212a0

## NSN 5315-00-890-0056

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.