## NSN 5315-00-896-6454

Pivot Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-896-6454

Canaral	Dagas	.:4		٠.
General	Desci	ามเ	101	ı.

No

0.812 in. Lg; 0.6862 ir	n. Min and 0.6866 in.	Maximum dia;	0.250-20 unc 3b thd;	0.4995 in. Min	and 0.4998 in.	Maximum shoulder dis	3; 45
degree chamfer 0.031	in. W; steel, cres as	stm a583; fassi	vate				

·	
$0.812 \; \text{in. Lg}; \;\; 0.6862 \; \text{in. Min and} \;\; 0.6866 \; \text{in. Maximum dia}; \;\; 0.250-20 \; \text{unc 3b thd}; \;\; 0.4995 \; \text{in. Min and} \;\; 0.4998 \; \text{in. Maximum shoulder dis}; \;\; 0.812 \; \text{in. Lg}; \;\; 0.6862 \; \text{in. Min and} \;\; 0.6866 \; \text{in. Maximum dia}; \;\; 0.250-20 \; \text{unc 3b thd}; \;\; 0.4995 \; \text{in. Min and} \;\; 0.4998 \; \text{in. Maximum shoulder dis}; \;\; 0.812 \; \text{in. Min and} \;\; 0.812 \; \text{in. Min and} \;\; 0.812 \; \text{in. Min and} \;\; 0.812 \; \text{in. Maximum dia}; \;\; 0.812 \; \text{in. Min and} \;\; 0.812 \; \text{in. Min and} \;\; 0.812 \; \text{in. Maximum dia}; \;\; 0.812 \; \text{in. Min and} \;\; 0.812 \; \text{in. Min and} \;\; 0.812 \; \text{in. Min and} \;\; 0.812 \; \text{in. Maximum dia}; \;\; 0.812 \; \text{in. Min and} \;\; 0.812 \; \text{in. Min and} \;\; 0.812 \; \text{in. Min and} \;\; 0.812 \; \text{in. Maximum dia}; \;\; 0.812 \; \text{in. Min and} \;\; 0.81$	45
degree chamfer 0.031 in. W; steel, cres astm a583; fassivate	
Shelf Life:	
N/a	
Unit Of Measure:	
<del></del>	
Demilitarization:	