# NSN 5315-00-899-4451

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-899-4451

## Head Diameter:

Between 0.805 inches and 0.870 inches

## Shank Diameter:

Between 0.6220 inches and 0.6235 inches

## **Detent Quantity:**

2

## **Actuation Method:**

Push button

#### Grip Length:

Between 1.300 inches and 1.320 inches

#### **Actuation Type:**

Pull and push

#### Hardness Rating:

40.0 rockwell c spindle

#### Shear Strength:

67500 double pounds per square inch

## Shoulder To Head End Distance:

1.465 inches

## Pin Center To Handle End Distance:

Between 1.685 inches and 1.810 inches

## Pin Attachment Type:

Link or ring

## Detent To Tapered End Distance:

Between 0.700 inches and 0.750 inches

Material:

Steel comp 631 spring or steel comp 302 spring

## **Material Specification:**

Qq-s-763 federal specification single material response detent

## Surface Treatment:

Passivate spring

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spring

## Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0

# NSN 5315-00-899-4451

Quick Release Pin - Page 2 of 2

Mil-std (military Standard):

Mil-a-8625 spec.

