

View Online at <https://aerobasegroup.com/nsn/5315-00-904-1663>

**Shank Diameter:**

Between 0.2470 inches and 0.2485 inches

**Button Handle Diameter:**

Between 0.720 inches and 0.800 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

Engine, aircraft, j-57 all models (c-135, ec-135, b-52); helicopter, mh-53e; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); support equipment, b-1; engine, aircraft tf33-p-3/5/9 (c/ec-135, b-52h); engine, aircraft, tf-33-p-7 (c-141a/b); engine, aircraft, f100-pw-200 (f-16a/b/c/d); aircraft, t-2; aircraft, ( ac-130h, mc-130h, ec-130e, hc-130)

**Grip Length:**

Between 0.900 inches and 0.920 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shoulder To Head End Distance:**

0.890 inches

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

Between 0.260 inches and 0.290 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0