

View Online at <https://aerobasegroup.com/nsn/5315-00-904-1663>

Shank Diameter:

Between 0.2470 inches and 0.2485 inches

Button Handle Diameter:

Between 0.720 inches and 0.800 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

Engine, aircraft, j-57 all models (c-135, ec-135, b-52); helicopter, mh-53e; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); support equipment, b-1; engine, aircraft tf33-p-3/5/9 (c/ec-135, b-52h); engine, aircraft, tf-33-p-7 (c-141a/b); engine, aircraft, f100-pw-200 (f-16a/b/c/d); aircraft, t-2; aircraft, (ac-130h, mc-130h, ec-130e, hc-130)

Grip Length:

Between 0.900 inches and 0.920 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

0.890 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.260 inches and 0.290 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0