

View Online at <https://aerobasegroup.com/nsn/5315-00-904-4781>

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Button Handle Diameter:

Between 1.300 inches and 1.400 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

W/s: engine, aircraft, f110-ge-100/129 (f-16c/d); support equipment, b-52 aircraft; engine, aircraft, f100-pw-200 (f-16a/b/c/d); support equipment, b-1 aircraft; general handling equipment; aircraft, galaxy c-5; aircraft, tomcat f-14; engine, aircraft, f110-ge-400; airborne mine counter measure systems; forrestal class cv

Grip Length:

Between 1.900 inches and 1.920 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shear Strength:

36800 double pound

Shoulder To Head End Distance:

1.190 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

0.460 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0