

View Online at <https://aerobasegroup.com/nsn/5315-00-904-4781>

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Button Handle Diameter:**

Between 1.300 inches and 1.400 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

W/s: engine, aircraft, f110-ge-100/129 (f-16c/d); support equipment, b-52 aircraft; engine, aircraft, f100-pw-200 (f-16a/b/c/d); support equipment, b-1 aircraft; general handling equipment; aircraft, galaxy c-5; aircraft, tomcat f-14; engine, aircraft, f110-ge-400; airborne mine counter measure systems; forrestal class cv

**Grip Length:**

Between 1.900 inches and 1.920 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

36800 double pound

**Shoulder To Head End Distance:**

1.190 inches

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

0.460 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0