

View Online at <https://aerobasegroup.com/nsn/5315-00-904-4785>

Shank Diameter:

Between 0.3720 inches and 0.3735 inches

Button Handle Diameter:

Between 0.875 inches and 1.135 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

W/s: aircraft, hx unique; missile, all-weather anti-ship, harpoon (agm-84); emory s. Land class as; los angeles class ssn (688); deck machinery; submarine armament and fire control systems; armanent system; missile, minuteman lgm-30; virginia class submarine ssn-774

Grip Length:

Between 1.900 inches and 1.920 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

1.040 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.335 inches and 0.365 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0