

View Online at <https://aerobasegroup.com/nsn/5315-00-904-6182>

Shank Diameter:

Between 0.3095 inches and 0.3110 inches

Button Handle Diameter:

Between 0.810 inches and 1.135 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

W/s: engine, aircraft f110-ge-400; m1a2 abrams tank, 2350-01-328-5964 (eaa cmbt85sep); m1a2 heavy assault bridge (hab)/wolverine, 5420-01-430-4247; m1a2 system enhancement prog 2350-01-328-5964 (eaa cmbt85sep); missile, minuteman lgm-30; aircraft, stratolifter c-135; tank, abrams m-1; troposcatter radio terminal system antrc170; tank, combat, ft, 120mm gun (m1a1); support equipment, mx peacekeeper missile

Grip Length:

Between 0.800 inches and 0.820 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shear Strength:

14400 double pound

Shoulder To Head End Distance:

0.930 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.300 inches and 0.330 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0