

View Online at <https://aerobasegroup.com/nsn/5315-00-904-6182>

**Shank Diameter:**

Between 0.3095 inches and 0.3110 inches

**Button Handle Diameter:**

Between 0.810 inches and 1.135 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

W/s: engine, aircraft f110-ge-400; m1a2 abrams tank, 2350-01-328-5964 (eaa cmbt85sep); m1a2 heavy assault bridge (hab)/wolverine, 5420-01-430-4247; m1a2 system enhancement prog 2350-01-328-5964 (eaa cmbt85sep); missile, minuteman lgm-30; aircraft, stratolifter c-135; tank, abrams m-1; troposcatter radio terminal system antrc170; tank, combat, ft, 120mm gun (m1a1); support equipment, mx peacekeeper missile

**Grip Length:**

Between 0.800 inches and 0.820 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

14400 double pound

**Shoulder To Head End Distance:**

0.930 inches

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

Between 0.300 inches and 0.330 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0