# NSN 5315-00-904-6185

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-904-6185

## Shank Diameter:

Between 0.4345 inches and 0.4360 inches

## **Button Handle Diameter:**

Between 0.940 inches and 1.400 inches

# **Detent Quantity:**

2

#### **Actuation Method:**

Push button

#### Grip Length:

Between 1.600 inches and 1.620 inches

#### Actuation Type:

Push

#### Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

#### Shear Strength:

25000 double pound

#### Shoulder To Head End Distance:

1.160 inches

## **Pin Attachment Type:**

Link or ring

# Detent To Tapered End Distance:

Between 0.350 inches and 0.380 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

#### **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

#### Surface Treatment:

Passivate spindle

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

#### Style Designator:

Button

Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A212a0