# NSN 5315-00-904-8266

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-904-8266

## Shank Diameter:

Between 0.3720 inches and 0.3735 inches

## **Detent Quantity:**

2

# **Actuation Method:**

Push button

## Grip Length:

Between 1.200 inches and 1.220 inches

## Actuation Type:

Push

## Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

#### Shear Strength:

18400 double pound

#### Shoulder To Head End Distance:

1.450 inches

## Pin Center To Handle End Distance:

1.640 inches

## **Pin Attachment Type:**

Hook or ring

## Detent To Tapered End Distance:

Between 0.335 inches and 0.365 inches

## Material:

Steel comp 4130 spindle

## **Material Specification:**

Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

## Surface Treatment:

Cadmium spindle and chromate spindle

## Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

## Style Designator:

L handle

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

# A212a0

Mil-std (military Standard):

Mil-t-6736 spec.