NSN 5315-00-905-2672

Headless Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-905-2672 First End Style: Chamfered **Overall Length:** Between 2.078 inches and 2.109 inches Diameter: Between 0.7496 inches and 0.7500 inches **Effective Length:** Between 1.790 inches and 1.810 inches **Undercut Diameter:** Between 0.701 inches and 0.707 inches **Undercut Width:** Between 0.046 inches and 0.049 inches **Second Undercut Width:** Between 0.046 inches and 0.049 inches First End Taper Length: Between 0.016 inches and 0.031 inches Second End Relationship With First End: Identical **First End Location:** Both ends First End Taper Angle: Between 40.0 degrees and 50.0 degrees **Surface Finish:** 100.0 microinches large shank **Special Features:** No. 3 maximum center drill optional both ends Material: Steel comp 1042 or steel comp 1141 **Material Specification:** Qq-s-624 federal specification all material responses **Surface Treatment:** Phosphate zinc **Surface Treatment Specification:** Mil-c-16232 type 2 military specification single treatment response **Style Designator:** Groove Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5315-00-905-2672

Headless Grooved Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-c-16232 spec.