## NSN 5315-00-912-2126

Headed Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-912-2126

		•	
ш	nod	Stv	Δ.
1 15	zau	JLV	œ.

Pan no. 2 (r1 not required in item description)

**Chamfer Length:** 

Between 0.077 inches and 0.109 inches

Diameter:

Between 0.869 inches and 0.871 inches

**Under Head Length:** 

Between 2.177 inches and 2.197 inches

**Hole Arrangement Style:** 

One end drilled

First Hole Diameter:

Between 0.161 inches and 0.181 inches

Distance From Centerline Of Hole To End Of Pin:

0.196 inches

**Hardness Rating:** 

26.5 rockwell c and 32.0 rockwell c

Pin Chamfer Angle:

Between 14.5 degrees and 15.5 degrees

**Shear Strength:** 

90200 double pound

**Pin Head Diameter:** 

Between 1.046 inches and 1.078 inches

**Special Features:** 

Shank end may have either a chamfer or radius at the option of the vendor

Height:

Between 0.109 inches and 0.141 inches

Material:

Steel comp 4037 or steel comp 4130 or steel comp 8630

**Material Specification:** 

Ams 6300 assn standard 1st material response or mil-s-6758 military specification 2nd material response or mil-s-6050 military specification 3rd material response

**Surface Treatment:** 

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2 cl 2 federal specification single treatment response

Style Designator:

Straight

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

## NSN 5315-00-912-2126

Headed Straight Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.