NSN 5315-00-915-2097

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-915-2097 **Head Diameter:** Between 0.310 inches and 0.530 inches **Shank Diameter:** Between 0.1870 inches and 0.1885 inches **Ring Handle Diameter:** 1.060 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 1.200 inches and 1.220 inches **Actuation Type:** Push **Hardness Rating:** 36.0 rockwell c spindle and 40.0 rockwell c spindle **Shear Strength:** 4600 double pounds per square inch **Shoulder To Head End Distance:** 0.730 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** Between 0.230 inches and 0.260 inches **Special Features:** Attaching hook or ring steel qq-w-428 or qq-w-423 form 1 cond a comp 302, passivated qq-p-35 Material: Steel spring **Material Specification:** Qq-w-470 federal specification single material response spring **Surface Treatment:** Passivate shank **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response shank **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5315-00-915-2097

Quick Release Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.