## NSN 5315-00-917-2658

Headless Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-917-2658 First End Style: Chamfered **Overall Length:** Between 2.271 inches and 2.291 inches Diameter: Between 0.4985 inches and 0.4990 inches **Effective Length:** Between 2.028 inches and 2.038 inches **Undercut Diameter:** Between 0.428 inches and 0.438 inches **Undercut Width:** Between 0.069 inches and 0.074 inches **Second Undercut Width:** Between 0.069 inches and 0.074 inches First End Taper Length: Between 0.005 inches and 0.025 inches Second End Relationship With First End: Identical **Hardness Rating:** 30.0 rockwell c and 35.0 rockwell c **First End Location:** Both ends First End Taper Angle: Between 40.0 degrees and 50.0 degrees **Surface Finish:** 16.0 microinches large shank Material: Steel comp 4140 **Material Specification:** Astm a322 assn standard single material response or astm a331 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Mil-p-16232, ty m, cl 1 military specification single treatment response **Style Designator:** Groove

N/a **Unit Of Measure:** 

Shelf Life:

**Demilitarization:** 

No

## NSN 5315-00-917-2658

Headless Grooved Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-p-16232 spec.