

View Online at <https://aerobasegroup.com/nsn/5315-00-922-1505>

**First End Style:**

Chamfered

**Second End Style:**

Square

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.500 inches

**Shank Length:**

Between 0.329 inches and 0.344 inches

**Shoulder Diameter:**

0.500 inches

**Shank Diameter:**

0.375 inches

**Overall Length:**

Between 0.829 inches and 0.844 inches

**Internal Drive Style:**

Slot

**First End Taper Length:**

0.062 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

23.0 rockwell c and 30.0 rockwell c

**Thread Size:**

0.500 inches

**First End Location:**

Short shank end

**First End Taper Angle:**

45.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 cond d military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.