NSN 5315-00-924-8065

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-924-8065

First End Styles
First End Style: Chamfered
Thread Class:
3a
Sa Thread Direction:
Right-hand
Thread Length: 0.375 inches
Shank Length:
0.500 inches
Shoulder Width Across Flats:
5.400 inches
Shank Diameter:
0.875 inches
Overall Length:
11.100 inches
Undercut Diameter:
0.750 inches
Undercut Width:
0.125 inches
Second Undercut Width:
0.125 inches
Second Undercut Diameter:
0.750 inches
Hole Arrangement Style:
Drilled through center
First Hole Diameter:
0.140 inches
First End Taper Length:
Between 0.040 inches and 0.070 inches
Thready Qty Per Inch (tpi):
14
Second End Relationship With First End:
Identical
Thread Size:
0.875 inches
Second Shank Diameter:
1.750 inches
First End Location:
Threaded end
First End Taper Angle:
Between 43.0 degrees and 47.0 degrees

NSN 5315-00-924-8065

Headless Shoulder Pin - Page 2 of 2



Second Shank Length: Between 0.302 inches and 0.332 inches Material: Steel comp e4340 **Material Specification:** Mil-s-5000 military specification single material response **Surface Treatment:** Nickel handle and chromate handlecadmium and chromate Style Designator: Undercut **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A212a0 Mil-std (military Standard): Mil-s-5000 spec.