

View Online at <https://aerobasegroup.com/nsn/5315-00-925-9768>

Head Diameter:

Between 0.410 inches and 0.590 inches

Shank Diameter:

Between 0.3095 inches and 0.3110 inches

Ring Handle Diameter:

1.060 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

Qw/s: oliver perry class ffg; arleigh burke class ddg; surface torpedo tubes & ordalts; support equip, c-17a aircraft; spruance class dd (963); ticonderoga class cg (47); fms- build frigates class ships; kidd class ddg

Grip Length:

Between 1.800 inches and 1.820 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

0.830 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.300 inches and 0.330 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0