## NSN 5315-00-928-2482

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-928-2482 **Head Diameter:** Between 0.510 inches and 0.630 inches **Shank Diameter:** Between 0.4345 inches and 0.4360 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 1.400 inches and 1.420 inches **Actuation Type:** Pull and push **Hardness Rating:** 40.0 rockwell c spindle **Shear Strength:** 28000 double pounds per square inch **Shoulder To Head End Distance:** 1.090 inches Pin Center To Handle End Distance: Between 1.375 inches and 1.500 inches Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** Between 0.460 inches and 0.510 inches Material: Steel comp 631 spring or steel comp 302 spring **Material Specification:** Qq-s-763 federal specification single material response detent **Surface Treatment:** Passivate spring **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spring **Style Designator:** L handle Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A212a0

## NSN 5315-00-928-2482

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.