NSN 5315-00-928-2483

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-928-2483 **Head Diameter:** Between 0.360 inches and 0.450 inches **Shank Diameter:** Between 0.2470 inches and 0.2485 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 3.600 inches and 3.620 inches **Actuation Type:** Pull and push **Hardness Rating:** 36.0 rockwell c spindle and 40.0 rockwell c spindle **Shear Strength:** 8200 double pounds per square inch **Shoulder To Head End Distance:** 1.030 inches Pin Center To Handle End Distance: Between 1.200 inches and 1.300 inches Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** Between 0.360 inches and 0.410 inches Material: Steel spring **Material Specification:** Qq-w-470 federal specification single material response spring **Surface Treatment:** Passivate handle **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response handle **Style Designator:** L handle Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A212a0

NSN 5315-00-928-2483

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.