## NSN 5315-00-928-2494

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-928-2494 **Head Diameter:** Between 0.360 inches and 0.450 inches **Shank Diameter:** Between 0.2470 inches and 0.2485 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 0.700 inches and 0.720 inches **Actuation Type:** Pull and push **Hardness Rating:** 36.0 rockwell c spindle and 40.0 rockwell c spindle **Shoulder To Head End Distance:** 1.030 inches Pin Center To Handle End Distance: Between 1.200 inches and 1.300 inches Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** Between 0.360 inches and 0.410 inches Material: Steel comp 4130 spindle **Material Specification:** Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle **Surface Treatment:** Cadmium spindle and chromate spindle **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response spindle **Style Designator:** L handle Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-t-6736 spec.