## NSN 5315-00-930-4209

Headless Straight Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-930-4209

| First End Style:                                |
|---|
| Chamfered                                       |
| Second End Style:                               |
| Chamfered                                       |
| Hole Arrangement Style:                         |
| Both end drilled                                |
| First Hole Diameter:                            |
| 0.375 inches                                    |
| Second Hole Diameter:                           |
| 0.377 inches                                    |
| Distance From Centerline Of Hole To End Of Pin: |
| Between 0.435 inches and 0.439 inches           |
| Center To Center Distance Between Holes:        |
| Between 1.624 inches and 1.628 inches           |
| Pinlength:                                      |
| 4.625 inches                                    |
| Pindiameter:                                    |
| Between 1.7480 inches and 1.7490 inches         |
| First End Taper Length:                         |
| 0.062 inches                                    |
| Second End Taper Length:                        |
| 0.125 inches                                    |
| Second End Relationship With First End:         |
| Not identical                                   |
| Hardness Rating:                                |
| 60.0 rockwell c and 62.0 rockwell c             |
| First End Taper Angle:                          |
| 45.0 degrees                                    |
| Second End Taper Angle:                         |
| 5.0 degrees                                     |
| Special Features:                               |
| 0.250 in. Diameter hole in center               |
| Material:                                       |
| Steel   |
| Shelf Life:                                     |
| N/a   |
| Unit Of Measure:                                |
|   |
| Demilitarization:                               |
| No  |
| Fiig:   |
| A212a0  |
|   |