NSN 5315-00-930-4713



Headed Grooved Pin - Page 1 of 2

Ticaded Grooved Fill Trage For 2	
View Online at https://aerobasegroup.com/nsn/5315-00-930-4713	
First End Style:	
Chamfered	
Head Style:	
Flat	
Diameter:	
Between 1.493 inches and 1.496 inches	
Effective Length:	
Between 3.867 inches and 3.872 inches	
Undercut Diameter:	
Between 1.245 inches and 1.255 inches	
Under Head Length:	
4.500 inches	
Undercut Radius:	
Between 0.128 inches and 0.133 inches	
Hole Arrangement Style:	
One end drilled	
First Hole Diameter:	
Between 0.281 inches and 0.291 inches	
Distance From Centerline Of Hole To End Of Pin:	
0.312 inches	
First End Taper Length:	
0.125 inches	
Grip Length:	
3.931 inches	
Hardness Rating:	
35.0 rockwell c and 40.0 rockwell c	
First End Taper Angle:	
45.0 degrees	
Pin Head Diameter:	
2.000 inches	
Surface Finish:	
125.0 microinches	
Height:	
0.188 inches	
Material:	
Steel comp 4140 or steel comp 8640	
Material Specification:	
Astm a304 assn standard single material response	

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

NSN 5315-00-930-4713

Headed Grooved Pin - Page 2 of 2



C+	_	_	~:~		-1-	
Styl	ıe	υe	SIC	ın	atc)r:
,				,		

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0