

View Online at <https://aerobasegroup.com/nsn/5315-00-930-6660>

Shank Diameter:

Between 0.1870 inches and 0.1885 inches

Button Handle Diameter:

Between 0.720 inches and 0.800 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

Support equipment, f-16 aircraft; aircraft, hornet f/a-18; aircraft, hercules c-130; support equipment, b-1 aircraft; missile, all-weather anti-ship, harpoon (agm-84); consolidated targets; support equipment, f-4 aircraft; helicopter, ch-53a/d/e; aircraft, harrier av-8b; helicopter, mh-53e

Grip Length:

Between 0.800 inches and 0.820 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

0.830 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.230 inches and 0.260 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0