

View Online at <https://aerobasegroup.com/nsn/5315-00-930-9747>

First End Style:

Chamfered

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.109 inches and 0.125 inches

Second Hole Diameter:

Between 0.109 inches and 0.125 inches

Distance From Centerline Of Hole To End Of Pin:

0.156 inches

Center To Center Distance Between Holes:

4.062 inches

Pinlength:

4.375 inches

Pindiameter:

Between 0.4030 inches and 0.4060 inches

First End Taper Length:

0.062 inches

Second End Relationship With First End:

Identical

Hardness Rating:

25.0 rockwell c and 32.0 rockwell c

First End Taper Angle:

45.0 degrees

Material:

Steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp 1046 or steel comp 1048 or steel comp 1049 or steel comp 1050 or steel comp 1137 or steel comp 1139 or steel comp 1140 or steel comp 1141

Surface Treatment:

Phosphate manganese

Surface Treatment Specification:

Mil-c-16232, tym, cl 2 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-c-16232 spec.