NSN 5315-00-932-1704

Headless Shoulder Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-932-1704

First End Style.ChamferedShank Length:Between 0.195 inches and 0.250 inchesShoulder Diameter:Between 0.245 inches and 0.255 inchesShank Diameter:Between 0.18725 inches and 0.18775 inchesOverall Length:Between 0.430 inches and 0.450 inchesFirst End Taper Length:0.060 inchesSecond End Relationship With First End:IdenticalSecond Shank Diameter:Between 0.187 inches and 0.188 inchesFirst End Location:Both endsFirst End Taper Angle:15.0 degreesSecond Shank Length:Between 0.195 inches and 0.250 inchesMaterial:Steel comp 321Material:Steel comp 321Material Specification:Ams 5645 assn standard single material responseSurface Treatment:PassivateShoulderShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:A212a0	First End Style:	
Shank Length: Between 0.195 inches and 0.250 inches Shoulder Diameter: Between 0.245 inches and 0.255 inches Shank Diameter: Between 0.18725 inches and 0.18775 inches Overall Length: Between 0.430 inches and 0.450 inches First End Taper Length: 0.060 inches Second End Relationship With First End: Identical Second Shank Diameter: Between 0.187 inches and 0.188 inches First End Location: Both ends First End Taper Angle: 15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Shoulder Shoulder Shoulder Shoulder Material: Na Stef Lifte: N/a Unit of Measure: - Demilitarization: No		
Between 0.195 inches and 0.250 inchesShoulder Diameter:Between 0.245 inches and 0.255 inchesShank Diameter:Between 0.18725 inches and 0.18775 inchesOverall Length:Between 0.430 inches and 0.450 inchesFirst End Taper Length:0.060 inchesSecond End Relationship With First End:IdenticalSecond Shank Diameter:Between 0.187 inches and 0.188 inchesFirst End Location:Both endsFirst End Taper Angle:15.0 degreesSecond Shank Length:Between 0.195 inches and 0.250 inchesMaterial:Steel comp 321Material Specification:Ams 5645 assn standard single material responseSurface Treatment:PassivateShoulderShoulderShoulderNaNaFirst DifficientNaFirst DifficientShoulderShoulderShoulderFirst DifficientNaFirst DifficientNaFirst DifficientNaShoulderFirst DifficientNaShoulderShoulderFirst DifficientNaFirst DifficientNaFirst DifficientNaFirst DifficientFirst DifficientFirst DifficientFirst DifficientFirst DifficientFirst DifficientFirst DifficientFirst Difficient		
Shoulder Diameter: Between 0.245 inches and 0.255 inches Shank Diameter: Between 0.18725 inches and 0.18775 inches Overall Length: Between 0.430 inches and 0.450 inches First End Taper Length: 0.060 inches Second End Relationship With First End: Identical Second Shank Diameter: Between 0.187 inches and 0.188 inches First End Location: Both ends First End Location: Both ends First End Taper Angle: 15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Shyle Designator: Shoulder Shelf Life: N/a Unit Of Measure: - Demilitarization: No		
Between 0.245 inches and 0.255 inches Between 0.245 inches and 0.255 inches Shank Diameter: Between 0.18725 inches and 0.18775 inches Overall Length: Between 0.430 inches and 0.450 inches First End Taper Length: 0.060 inches Second End Relationship With First End: Identical Second Shank Diameter: Between 0.187 inches and 0.188 inches First End Location: Both ends First End Taper Angle: 15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Shoulder Shoulder Material: N/a Unit Of Measure: Demilitarization: No Fiig:		
Shank Diameter: Between 0.18725 inches and 0.18775 inches Overall Length: Between 0.430 inches and 0.450 inches First End Taper Length: 0.060 inches Second End Relationship With First End: Identical Second Shank Diameter: Between 0.187 inches and 0.188 inches First End Location: Both ends First End Taper Angle: 15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Style Designator: Shoulder Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Between 0.18725 inches and 0.18775 inches Overall Length: Between 0.430 inches and 0.450 inches First End Taper Length: 0.060 inches Second End Relationship With First End: Identical Second Shank Diameter: Between 0.187 inches and 0.188 inches First End Location: Both ends First End Taper Angle: 15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Style Designator: Shoulder Shoulder Material: N/a Unit Of Measure: Demilitarization: No		
Overall Length:Between 0.430 inchess and 0.450 inchessFirst End Taper Length:0.060 inchesSecond End Relationship With First End:IdenticalBetween 0.187 inches and 0.188 inchesFirst End Location:Both endsFirst End Location:Both endsSecond Shank Length:Between 0.195 inches and 0.250 inchesMaterial:Steel comp 321Material Specification:Ams 5645 assn standard single material responseSurface Treatment:PassivateShelf Life:N/aUnit Of Measure:Panilitarization:NoFiig:		
Between 0.430 inches and 0.450 inches First End Taper Length: 0.060 inches Second End Relationship With First End: Identical Getween 0.187 inches and 0.188 inches First End Location: Both ends First End Taper Angle: 15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Shoulder Shell Life: N/a Unit Of Measure: Tomailitarization: No Fig:		
First End Taper Length: 0.060 inches Second End Relationship With First End: Identical Second Shank Diameter: Between 0.187 inches and 0.188 inches First End Location: Both ends First End Taper Angle: 15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Style Designator: Shoulder Shell Life: N/a Unit Of Measure: Demilitarization: No Fig:		
0.060 inches Second End Relationship With First End: Identical Second Shank Diameter: Between 0.187 inches and 0.188 inches First End Location: Both ends First End Taper Angle: 15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: No Fig:		
Second End Relationship With First End: Identical Second Shank Diameter: Between 0.187 inches and 0.188 inches First End Location: Both ends First End Taper Angle: 15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Style Designator: Shoulder Sheif Life: N/a Unit Of Measure: Demilitarization: No		
Identical Second Shank Diameter: Between 0.187 inches and 0.188 inches First End Location: Both ends First End Taper Angle: 15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
Second Shank Diameter: Between 0.187 inches and 0.188 inches First End Location: Both ends First End Taper Angle: 15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No	- -	
Between 0.187 inches and 0.188 inches First End Location: Both ends First End Taper Angle: 15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No		
First End Location: Both ends First End Taper Angle: 15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Both ends First End Taper Angle: 15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No		
First End Taper Angle: 15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No		
15.0 degrees Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
Second Shank Length: Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Between 0.195 inches and 0.250 inches Material: Steel comp 321 Material Specification: Ams 5645 assn standard single material response Surface Treatment: Passivate Passivate Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-	
Material:Steel comp 321Material Specification:Ams 5645 assn standard single material responseSurface Treatment:PassivateStyle Designator:ShoulderShelf Life:N/aUnit Of Measure:NoFig:		
Material Specification:Ams 5645 assn standard single material responseSurface Treatment:PassivateStyle Designator:ShoulderShelf Life:N/aUnit Of Measure:NoFig:		
Material Specification:Ams 5645 assn standard single material responseSurface Treatment:PassivateStyle Designator:ShoulderShelf Life:N/aUnit Of Measure:NoFig:	Steel comp 321	
Ams 5645 assn standard single material response Surface Treatment: Passivate Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:		
Surface Treatment: Passivate Style Designator: Shoulder Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ams 5645 assn standard single material response	
Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:	
Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Passivate	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:	
N/a Unit Of Measure: Demilitarization: No Fiig:	Shoulder	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
-	No	
A212a0	Fiig:	
	A212a0	